

CRUSHPROOF® TUBING

M.O.D.O.R. HOSE

Crushproof®'s MODOR (Multipurpose Overhead Drop Or Reel) series hose combines the best of both worlds for overhead drop systems or reel applications. The first 20' is a lightweight, reinforced hose and the last 5' is our 100% rubber hose with an included adapter. This design lets our rubber blend take the brunt of the heat and prevents damage in the most commonly run-over section of an overhead hose.

Stock sizes are 4", 5", and 6" ID x 25' length, and Custom ID's and lengths are also available. MODOR hoses are rated to 570°F when used with a fan assisted system.

MATERIALS

20' Lightweight Section:

Hose Wall: unique high temperature film.

External Helix: 4" hose uses crush-resistant plastic helix. 5" & 6" hoses use galvanized steel with a plastic abrasion protection layer.

5' Rubber Section:

Solid, crush-proof EPDM construction.



Part No.	I.D.	Length	Bend Radius	Weight	Adapter	Negative (in. w.c.)
MODOR-4	4"	25'	4.0"	25 lbs	F700	72
MODOR-5	5"	25'	3.0"	29 lbs	DSR600	20
MODOR-6	6"	25'	3.6"	33 lbs	DSR8600	14

LIGHTWEIGHT HOSE



ADAPTER



RUBBER HOSE



CRUSHPROOF TUBING COMPANY

Phone: 800-654-6858 or 419-293-2111

Fax: 419-293-2609

Email: contact49@crushproof.com

Location: 100 North Street McComb, Ohio 45858

crushproof.com

OR

SCAN THE QR CODE
FOR DIRECT ACCESS
TO OUR WEBSITE

