

FORCED AIR DIESEL & KEROSENE



- DEWALT TOUGH® design
- Multi-fuel capability; Kerosene, JP8, #1 and #2 Diesel, #1 and #2 Fuel Oil
- Cold weather start (0° F)
- Overheat safety shut-off
- Continuous ignition
- Fuel gauge
- Thermostat
- 1" tubular roll cage and barrel support
- Foam-filled flat-free tires
- CSA Certified
- Roll cage
- Barrel support/storage box
- Recessed knobs



Model #	DXH50K	DXH75KT	DXH135HD	DXH190HD	DXH215HD
Stock#	F340670	F340675	F340690	F340695	F340700
UPC	856795406707	856795406752	856795406905	856795406950	856795407001
BTU Output	50,000	75,000	135,000	190,000	215,000
*Heats Up To: (Approx. Sq. Ft.)	1,200	1,750	3,500	4,200	6,500
Run Time: (Approx.)	11 Hrs	11 Hrs.	9.5 Hrs	10 Hrs.	9.5 Hrs.
CFM Output	165	240	275	400	400
Tank Size (Gallon)	4	6	14	14	14
Thermostat	Sold Separately	Included	Included	Included	Included
Tires	N/A	N/A	Foam filled flat-free	Foam filled flat-free	Foam filled flat-free
Weight	33.75 lbs.	39 lbs.	60 lbs.	74 lbs.	106.5 lbs.
Shipping Ctn Size (In Inches)	32.5 x 14.25 x 14.75	32.25 x 14.25 x 17	39.75 x 18.25 x 20.75	39.75 x 18 x 21	42 x 18 x 22

* Heating area based on average insulation, ceiling height and desired temperature rise.

