



JTM-2 Mill With ACU-RITE 203 DRO and X-Axis Powerfeed

Product Images



Short Description

JTM-2 Mill With ACU-RITE 203 DRO and X-Axis Powerfeed

Additional Information

Stock Number	JT9-690114-2
Collet Capacity	1/8 - 7/8
Distance Spindle to Column (Max.) (In.)	19
Max Distance Spindle to Table (In.)	17-1/2
Model Number	JTM-2
Motor (HP)	2 HP, 115/230V, 1Ph
Number of Axis	2
Number of Spindle Speeds	8
Overall Dimensions (L x W x H) (In.)	57 x 64 x 82
Powerfeed	X-Axis
Prop 65	Cancer and Reproductive Harm
Quill Diameter (In.)	3-3/8
Quill Down Feed Rates (IPR)	.0015 - .003 - .006
Range of Spindle Speeds (RPM)	80 - 2,720
Spindle Taper (In. x TPI)	R-8
Spindle Travel (In.)	5
Style (Type)	Step Pulley R8
T-Slot Centers (In.)	2-1/2
Table Cross Travel (In.)	12-1/2
Table Longitudinal Travel (In.)	23-7/8
Table Longitudinal Travel With Powerfeed (In.)	20-2/7
Table Size (L x W) (In.)	9 x 42
Travel of Knee (In.)	14-1/2
Travel of Ram (In.)	13-3/8

Warranty	2 Year
Work Table Weight Capacity (Lbs.)	550
Gross Weight	2200.0
Net weight	2200.0

