



# USER MANUAL

## UR300QVAC AND UR300QVAC-PR1

### AUTOMATIC DUSTLESS VACUUM SYSTEMS



CORPORATION

[WWW.UNIRAM.COM](http://WWW.UNIRAM.COM)

- 381 Bentley Street, Markham ON L3R 9T2
- Tel. 1-800-417-9133
- [sales@uniram.com](mailto:sales@uniram.com)

REVISED 2019-05

Follow these procedures to operate this machine safely and effectively. Ensure that this manual is readily available to the operator at all times. If you have any questions about the operation of this machine, contact:

North America: Uni-ram Technical Service 1-800-417- 9133  
Other Continents: Contact Your Supplier

### MODELS

| MODEL   | UR300QVAC              | UR300QVAC-PR1          |
|---------|------------------------|------------------------|
| VOLTAGE | 120 V, 50/60 HZ, 800 W | 120 V, 50/60 HZ, 800 W |
| SANDERS | NOT INCLUDED           | 1 SANDER               |

### FEATURES AND SPECIFICATIONS

These mobile vacuums are ideally suited for automotive, marine and industrial applications wherever air operated, vacuum-assist tools are used.

- Portable.
- 120 V, 50/60 Hz, 800 W.
- 20 foot power cord, 16 foot vacuum hose.
- Automatic activation of vacuum by air tool, manual override.
- 1 motor 800 W; Maximum decibel rating is 60 db. Wattage (power consumption) can be reduced using the Variable Power Adjustment dial.
- For use with disposable garbage bags.
- There is a bag filter and a Single Cartridge Filter which is standard. High Density Filters are available.
- Electrical outlet for use with one electrical sander.
- Sealed Vacuum: 87" water (2200mm)
- Supply air pressure: 100 PSI(6.5 bar)
- Motor is a bypass, 2 stage motor for long life and vacuum power. Die cast housing. Internal fan for cooling.
- Shipping Dimensions (WDH): 22 X 20 X 32"
- Weight: 47 lb / 21 kg

### CATUTIONS AND WARNINGS

- **Use this vacuum with non-hazardous dust. DO NOT use this vacuum with ignitable hazardous dust including alumina and magnesia. Do not use this vacuum with flammable liquids like gasoline.**
- **Repair must be carried out by a qualified technician.**