



1/2" DRIVE DEEP SOCKETS, 12 POINT, METRIC

High-Polished Chrome Finish

		A	B	C	D	E		F
Product Code	Size (MM)	OAL (Inches)	Drive End Diameter (Inches)	Working End Diameter (Inches)	Broach Depth (Inches)	Bolt Clearance Depth (Inches)	Bolt Clearance Diameter (Inches)	Nose Length (Inches)
32809	9	3 1/4	29/32	19/32	5/16	2 15/32	11/32	2 19/32
32810	10	3 1/4	29/32	19/32	5/16	2 15/32	11/32	2 19/32
32811	11	3 1/4	29/32	1 1/16	5/16	2 15/32	13/32	2 19/32
32812	12	3 1/4	29/32	23/32	13/32	2 15/32	7/16	2 19/32
32813	13	3 1/4	29/32	25/32	3/8	2 15/32	15/32	2 19/32
32814	14	3 1/4	29/32	27/32	3/8	2 15/32	15/32	2 19/32
32815	15	3 1/4	29/32	7/8	3/8	2 11/32	15/32	-
32816	16	3 1/4	29/32	29/32	9/16	2 11/32	15/32	-
32817	17	3 1/4	31/32	31/32	9/16	2 11/32	15/32	-
32818	18	3 1/4	1	1	13/16	2 11/32	15/32	-
32819	19	3 1/4	1 1/32	1 1/32	13/16	2 5/16	23/32	-
32820	20	3 1/4	1 1/16	1 1/16	13/16	2 5/16	23/32	-
32821	21	3 1/4	1 1/8	1 1/8	13/16	2 5/16	3/4	-
32822	22	3 1/4	1 3/16	1 3/16	13/16	2 5/16	23/32	-
32823	23	3 1/4	1 1/4	1 1/4	25/32	2 5/16	27/32	-
32824	24	3 1/4	1 9/32	1 9/32	13/16	2 5/16	7/8	-
32825	25	3 1/4	1 5/16	1 5/16	13/16	2 1/4	15/16	-
32826	26	3 1/4	1 3/8	1 3/8	29/32	2 1/4	31/32	-
32827	27	3 1/4	1 7/16	1 7/16	31/32	2 1/4	1	-
32828	28	3 1/4	1 1/2	1 1/2	1	2 1/4	1 1/32	-
32829	29	3 1/4	1 9/16	1 9/16	1 1/32	2 1/4	1 1/16	-
32830	30	3 1/4	1 5/8	1 5/8	1 1/32	2 1/4	1 3/32	-
32832	32	3 1/4	1 11/16	1 11/16	1 1/8	2 1/4	1 3/16	-
32834	34	3 1/4	1 3/4	1 3/4	7/8	2 1/4	1	-
32836	36	3 1/4	1 15/16	1 15/16	7/8	2 1/4	1 13/32	-

Fed. Spec: ANSI B107.110

32951 16 Piece 1/2" Drive Deep 12 Point Socket Set on Clip Rail

Contents Include:

Product Code	Size (MM)	Product Code	Size (MM)	Product Code	Size (MM)	Product Code	Size (MM)
32809	9	32813	13	32817	17	32821	21
32810	10	32814	14	32818	18	32822	22
32811	11	32815	15	32819	19	32823	23
32812	12	32816	16	32820	20	32824	24



32949 24 Piece 1/2" Drive Deep 12 Point Socket Set on Clip Rail

Contents Include:

Product Code	Size (MM)	Product Code	Size (MM)	Product Code	Size (MM)	Product Code	Size (MM)
32809	9	32815	15	32821	21	32827	27
32810	10	32816	16	32822	22	32828	28
32811	11	32817	17	32823	23	32829	29
32812	12	32818	18	32824	24	32830	30
32813	13	32819	19	32825	25	32832	32
32814	14	32820	20	32826	26	32836	36



Features

- SUPERTORQUE[®] lobular openings for greater turning power without deforming the fastener.
- Designed for quick engagement on both 6 and 12 point fasteners.