



1/2" DRIVE SHALLOW IMPACT SOCKETS, 6 POINT, SAE

Black Industrial Finish

		A	B	C	D	E	F	
Product Code	Size (Inches)	OAL (Inches)	Drive End Diameter (Inches)	Working End Diameter (Inches)	Broach Depth (Inches)	Bolt Clearance Depth (Inches)	Bolt Clearance Diameter (Inches)	Nose Length (Inches)
37112	3/8	1 1/2	15/16	5/8	9/16	7/8	5/16	3/4
37114	7/16	1 1/2	15/16	23/32	9/16	13/16	13/32	3/4
37116	1/2	1 1/2	15/16	13/16	9/16	21/32	15/32	3/4
37118	9/16	1 1/2	15/16	7/8	9/16	27/32	17/32	3/4
37120	5/8	1 1/2	1	31/32	1/2	29/32	9/16	3/4
37122	11/16	1 1/2	1 1/8	1 1/32	17/32	29/32	21/32	3/4
37124	3/4	1 1/2	1 1/8	1 1/8	3/4	29/32		-
37126	13/16	1 1/2	1 3/16	1 3/16	3/4	29/32		-
37128	7/8	1 1/2	1 1/4	1 1/4	3/4	15/16		-
37130	15/16	1 3/4	1 3/8	1 3/8	1	17/32		-
37132	1	1 3/4	1 1/2	1 1/2	1	17/32		-
37134	1 1/16	1 3/4	1 17/32	1 17/32	1	17/32		-
37136	1 1/8	1 3/4	1 5/8	1 5/8	1	1 3/16		-
37138	1 3/16	1 3/4	1 5/8	1 5/8	1	1 3/16		-
37140	1 1/4	1 3/4	1 3/4	1 3/4	1	1 5/32		-
37142	1 5/16	1 3/4	1 7/8	1 7/8	31/32	31/32	1 7/32	-
37144	1 3/8	2	1 57/64	1 57/64	1 1/16	1 1/16	1 19/64	-
37146	1 7/16	2	1 31/32	1 31/32	1 1/16	1 1/16	1 11/32	-
37148	1 1/2	2	2 1/8	2 1/8	1 1/16	1 1/16	1 3/8	-

Fed. Spec: ANSI B107.2

37902 9 Piece 1/2" Drive Shallow 6 Point Impact Socket Set on Clip Rail

Contents Include:

Product Code	Size (Inches)	Product Code	Size (Inches)	Product Code	Size (Inches)
37116	1/2	37122	11/16	37128	7/8
37118	9/16	37124	3/4	37130	15/16
37120	5/8	37126	13/16	37132	1

37904 14 Piece 1/2" Drive Shallow 6 Point Impact Socket Set on Clip Rail

Contents Include:

Product Code	Size (Inches)	Product Code	Size (Inches)	Product Code	Size (Inches)
37112	3/8	37122	11/16	37132	1
37114	7/16	37124	3/4	37134	1 1/16
37116	1/2	37126	13/16	37136	1 1/8
37118	9/16	37128	7/8	37140	1 1/4
37120	5/8	37130	15/16		

37905 19 piece 1/2" Drive Impact Shallow 6 Point Socket Set on Clip Rails

Contents Include:

Product Code	Size (Inches)	Product Code	Size (Inches)	Product Code	Size (Inches)	Product Code	Size (Inches)
37112	3/8	37122	11/16	37132	1	37142	1 5/16
37114	7/16	37124	3/4	37134	1 1/16	37144	1 3/8
37116	1/2	37126	13/16	37136	1 1/8	37146	1 7/16
37118	9/16	37128	7/8	37138	1 3/16	37148	1 1/2
37120	5/8	37130	15/16	37140	1 1/4		

Features

- SUPERTORQUE® lobular openings for greater turning power without deforming the fastener.
- Designed for maximum engagement on 6 point fasteners.
- Suitable for use with pneumatic and electric impact wrenches.
- Specially heat treated for impact use to provide long life, safety, and durability.
- Drive end features pin retention hole and groove.



37112, 37124




Side hole in socket permits use with Snap-on Industrial Brands Tools@Height drive tools such as ratchets, extensions and u-joints



37902



37904



37905