


3/4" DRIVE SHALLOW IMPACT SOCKETS, 12 POINT, SAE

Black Industrial Finish

	A	B	C	D	E	F
Product Code	Size (Inches)	Overall Length (Inches)	Drive End Diameter (Inches)	Working End Diameter (Inches)	Broach Depth (Inches)	Nose Length (Inches)
38420	5/8	2	1 1/2	1 1/8	5/8	7/8
38422	11/16	2	1 1/2	1 1/8	5/8	7/8
38424	3/4	2	1 1/2	1 1/8	5/8	7/8
38426	13/16	2 1/16	1 1/2	1 1/4	3/4	15/16
38428	7/8	2 1/16	1 1/2	1 5/16	3/4	15/16
38430	15/16	2 1/16	1 1/2	1 7/16	3/4	15/16
38432	1	2 1/16	1 1/2	1 1/2	3/4	15/16
38434	1 1/16	2 1/16	1 1/2	1 1/2	3/4	15/16
38436	1 1/8	2 1/16	1 5/8	1 5/8	3/4	15/16
38438	1 3/16	2 1/16	1 3/4	1 3/4	3/4	15/16
38440	1 1/4	2 1/16	1 3/4	1 13/16	3/4	15/16
38442	1 5/16	2 1/4	1 3/4	1 13/16	7/8	15/16
38444	1 3/8	2 1/4	1 3/4	2	7/8	15/16
38446	1 7/16	2 1/4	1 3/4	2	7/8	15/16
38448	1 1/2	2 1/4	1 3/4	2 1/16	15/16	15/16
38450	1 9/16	2 1/16	1 3/4	2 1/4	15/16	1
38452	1 5/8	2 7/16	1 3/4	2 1/4	15/16	1
38454	1 11/16	2 7/16	1 3/4	2 1/2	1 1/16	1
38456	1 3/4	2 7/16	1 3/4	2 1/2	1 1/16	1
38458	1 13/16	2 5/8	1 3/4	2 5/8	1 1/16	1
38460	1 7/8	2 5/8	1 3/4	2 5/8	1 1/16	1
38462	1 15/16	2 3/4	1 3/4	2 3/4	1 5/16	1
38464	2	2 13/16	2 1/8	2 3/4	1 5/16	1
38466	2 1/16	2 13/16	2 1/8	3	1 5/16	1
38468	2 1/8	2 13/16	2 1/8	3	1 5/16	1
38476	2 3/8	3	2 1/8	3 5/16	1 1/2	1 1/16



38925 9 piece 3/4" Drive Impact Shallow 12 Point, SAE Socket Set on Clip Rails

Contents Include:

Product Code	Size (Inches)	Product Code	Size (Inches)	Product Code	Size (Inches)
38420	5/8	38426	13/16	38432	1
38422	11/16	38428	7/8	38434	1 1/16
38424	3/4	38430	15/16	38436	1 1/8

38926 17 piece 3/4" Drive Impact Shallow 12 Point, SAE Socket Set on Clip Rails

Contents Include:

Product Code	Size (Inches)	Product Code	Size (Inches)	Product Code	Size (Inches)	Product Code	Size (Inches)
38438	1 3/16	38446	1 7/16	38454	1 11/16	38462	1 15/16
38440	1 1/4	38448	1 1/2	38456	1 3/4	38464	2
38442	1 5/16	38450	1 9/16	38458	1 13/16	38466	2 1/16
38444	1 3/8	38452	1 5/8	38460	1 7/8	38468	2 1/8
						38476	2 3/8



38925

Features

- SUPERTORQUE® lobular openings for greater turning power without deforming the fastener.
- Designed for maximum engagement on 6 or 12 point fasteners.
- Suitable for use with pneumatic and electric impact wrenches.
- Specially heat treated for impact use to provide long life, safety, and durability.