


1-1/2" DRIVE SHALLOW IMPACT SOCKETS, 12 POINT, SAE

Black Industrial Finish

Product Code	Size (Inches)	A Overall Length (Inches)	B Drive End Diameter (Inches)	C Working End Diameter (Inches)	D Broach Depth (Inches)	E Bolt Clearance Depth (Inches)	Bolt Clearance Diameter (Inches)	F Nose Length (Inches)
41144	1 3/8	3 1/8	3 3/8	2 1/2	1	/	1 3/16	1 3/8
41146	1 7/16	3 1/8	3 3/8	2 1/2	1	/	1 1/4	1 3/8
41148	1 1/2	3 1/8	3 3/8	2 5/8	1	/	1 1/4	1 3/8
41150	1 9/16	3 1/8	3 3/8	2 5/8	1	/	1 3/8	1 3/8
41152	1 5/8	3 1/8	3 3/8	2 3/4	1	/	1 3/8	1 3/8
41154	1 11/16	3 1/4	3 3/8	2 3/4	1 1/16	/	1 1/2	1 1/2
41156	1 3/4	3 1/4	3 3/8	2 15/16	1 1/16	/	1 1/2	1 1/2
41158	1 13/16	3 1/4	3 3/8	2 15/16	1 1/16	/	1 5/8	1 1/2
41160	1 7/8	3 7/16	3 3/8	3 1/8	1 3/16	/	1 5/8	1 5/8
41162	1 15/16	3 7/16	3 3/8	3 1/8	1 3/16	/	1 3/4	1 5/8
41164	2	3 7/16	3 3/8	3 1/4	1 3/16	/	1 3/4	1 5/8
41166	2 1/16	3 7/16	3 3/8	3 1/4	1 3/16	/	1 7/8	1 5/8
41168	2 1/8	3 1/2	3 3/8	3 3/8	1 1/2	/	1 7/8	/
41170	2 3/16	3 1/2	3 3/8	3 3/8	1 1/2	/	1 7/8	/
41172	2 1/4	3 1/2	3 3/8	3 5/8	1 1/2	/	2 1/16	1 3/4
41174	2 5/16	3 1/2	3 3/8	3 5/8	1 1/2	/	2 1/16	1 3/4
41176	2 3/8	3 1/2	3 3/8	3 5/8	1 1/2	/	2 1/16	1 3/4
41178	2 7/16	3 3/4	3 3/8	3 7/8	1 5/8	/	3/4	1 3/4
41180	2 1/2	3 3/4	3 3/8	3 7/8	1 5/8	/	3/4	1 3/4
41182	2 9/16	3 3/4	3 3/8	3 7/8	1 5/8	/	3/4	1 3/4
41184	2 5/8	3 3/4	3 3/8	4 3/16	1 5/8	/	2 7/16	1 3/4
41186	2 11/16	3 3/4	3 3/8	4 3/16	1 5/8	/	2 7/16	1 3/4
41188	2 3/4	3 3/4	3 3/8	4 3/16	1 5/8	/	2 1/2	1 3/4
41190	2 13/16	4 1/16	3 3/8	4 1/4	1 3/4	/	2 1/2	1 3/4
41192	2 7/8	4 1/16	3 3/8	4 1/4	1 3/4	/	2 5/8	1 3/4
41194	2 15/16	4 1/16	3 3/8	4 1/4	1 3/4	/	2 5/8	1 3/4
41196	3	4 1/4	3 3/8	4 5/8	2	/	2 3/4	1 3/4
41200	3 1/8	4 1/4	3 3/8	4 5/8	2	/	2 3/4	1 3/4
41204	3 1/4	4 1/4	3 3/8	4 15/16	2	/	3	1 3/4
41208	3 3/8	4 1/4	3 3/8	4 15/16	2	/	3	1 3/4
41212	3 1/2	4 5/8	3 3/8	5	2 3/16	/	3 1/4	1 3/4
41220	3 3/4	4 5/8	3 3/4	5 1/4	2 3/16	/	3 1/2	2
41224	3 7/8	4 15/16	3 3/4	5 7/16	2 1/4	/	3 5/8	2
41226	3 15/16	4 15/16	3 3/4	5 7/16	2 1/4	/	3 5/8	2
41228	4	4 15/16	3 3/4	5 7/16	2 1/4	/	3 3/4	2



41144



Features

- SUPERTORQUE® lobular openings for greater turning power without deforming the fastener.
- Designed for maximum engagement on 6 and 12 point fasteners.
- Suitable for use with pneumatic and electric impact wrenches.
- Specially heat treated for impact use to provide long life, safety, and durability.