



4T06T



4T10T

WILLIAMS®

TOE JACKS

- Heat treated and chrome plated medium-carbon steel cylinder
- Chrome plated ram promotes longer seal life and optimum performance
- U.S. Patented by-pass device protects hydraulic system from over traveling damage

TOE JACK DIMENSIONS

Capacity [tons]	Product Code	Toe Saddle		Head Saddle		Hydraulic Lifting [in]
		Min. Height [in]	Max. Height [in]	Min. Height [in]	Max. Height [in]	
6	4T06T	0.88	6.00	10.50	15.63	5.13
10	4T10T	1.13	6.25	11.00	16.13	



3S20TV

WILLIAMS®

SIDE PUMP BOTTLE JACK

- Hydraulic system is protected from internal damage by a patented by-pass mechanism
- Machined and polished cylinders with die-cut threads provide non-abrasive leak-free, durable performance
- Fabricated from hard-cast steel with heat-treated critical stress areas
- Serrated heat-treated saddle provides generous lifting area and secure grip
- Heat-treated extension screw allows low pick-up height adjustment and maximum lift height
- U.S. patented built-in by-pass device protects hydraulic system from overpumping damage
- Unique cross-type forged release valve assures positive control
- A wide, rugged base provides stability and strength
- Critical stress points are reinforced in all models for added durability and dependability
- Economically priced for maximum value

SIDE PUMP BOTTLE JACK DIMENSIONS

Capacity [tons]	Product Code	Min. Height [in]	Max. Height [in]	Extension Screw [in]	Hydraulic Lifting [in]	Base Size (L x W) [in]
12	3T12TV	9.50	18.63	3.13	6.00	5.25 x 5.13
	3S12TV	6.00	10.63	1.63	3.00	
20	3T20TV	9.50	18.63	3.13	6.00	6.25 x 5.88
	3S20TV	6.50	11.25	1.63	3.13	