



## JHWISSX920

**1/2 Drive 5/8 6 Point Flexextension,  
Black Industrial Finish, (Non-  
Tension) 9" Shank Length**



### PRODUCT DETAILS

- Made in the U.S.A
- Durable black oxide finish
- Socket retention pin is TIG welded, providing full rotation power to the socket
- Sockets feature SUPERTORQUE® lobular openings for greater turning power without deforming the fastener
- Drive end has a 7/32" cross hole & bevel for ease of use
- Up to 30 degree angle offset
- Flexextensions are designed for use on hand and power tools (Impulse or Direct drive); NOT FOR IMPACT TOOL USE
- Maximum working torque values: 160 ft-lbs. /1920 in-lbs. /217 Nm
- Other lengths and socket sizes available by special order. Contact your Williams representative

### PRODUCT ATTRIBUTES

| Product    |  | A               |  |  |  | B            | C              | D              | E              |  |
|------------|-------------------------------------------------------------------------------------|-----------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|--------------|----------------|----------------|----------------|---------------------------------------------------------------------------------------|
| JHWISSX920 | 1/2 in                                                                              | 9.57in/243.1 mm | No                                                                                  | 6                                                                                   | 5/8 in                                                                              | 1.06/26.9 mm | 0.90in/22.7 mm | 0.90in/22.7 mm | 0.44in/11.2 mm | 0.73 lb                                                                               |