



## JHWISSXT412

**1/2 Drive 3/8 6 Point Flexextension,  
Black Industrial Finish, (Tension)  
4" Shank Length**



### PRODUCT DETAILS

- Made in the U.S.A
- Durable black oxide finish
- Socket retention pin is TIG welded, providing full rotation power to the socket
- Sockets feature SUPERTORQUE® lobular openings for greater turning power without deforming the fastener
- Drive end has a 7/32" cross hole & bevel for ease of use
- Up to 30 degree angle offset
- Flexextensions are designed for use on hand and power tools (Impulse or Direct drive); NOT FOR IMPACT TOOL USE
- Maximum working torque values: 160 Ft. Lbs. /1920 In. Lbs. /217 Nm
- Other lengths and socket sizes available by special order. Contact your Williams representative

### PRODUCT ATTRIBUTES

| Product     |  | A               |  |  |  | B            | C              | D              | E             |  |
|-------------|-------------------------------------------------------------------------------------|-----------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|--------------|----------------|----------------|---------------|---------------------------------------------------------------------------------------|
| JHWISSXT412 | 1/2 in                                                                              | 4.09in/103.9 mm | Yes                                                                                 | 6                                                                                   | 3/8 in                                                                              | 1.06/26.9 mm | 0.90in/22.7 mm | 0.63in/16.0 mm | 0.28in/7.1 mm | 0.49 lb                                                                               |