

AutobradeRed® FOR THE VALUE-MINDED PRO

3" Dia., Right Angle Buffer

- Uses 3" diameter buffs. Built-in speed control, rear exhaust.
- 3/8"-24 male spindle. Safety-lock lever throttle.
- Composite comfort grip reduces cold air transmission to the operator.
- Includes 50126 Back-Up Pad (3" dia. hook-face) and 90034 Wool Buff (3-1/2" dia.).
- Ideal for small areas where full size buffers are too big.
- Polish aluminum wheels, side view mirrors and more.
- Buffing pad selection on page 44.

Model 18055

2,400 RPM

Model 18056

3,200 RPM



3" Dia., Right Angle Buffer/Spot Sander Kit

18058

- Excellent tool for spot repair and buffing/polishing. Angle-head design permits access to difficult areas.

Includes:

- 18055 2,400 RPM tool
- 50122 3" Hook-Face Backing Pad (3/8"-24)
- 90027 3" Terry Cloth Bonnet
- 90028 3" Synthetic Wool Pad
- 90034 3" Natural Wool Pad
- 90038 3" White Polishing Foam Pad
- 90044 3" Yellow Cutting Foam Pad
- 95723 4 oz. Finesse Creme
- 95727 4 oz. Dynabrade Glaze
- 54034 Random Orbit Sanding Head
- 54018 1-1/4" Sanding Pad
- 93191 Sample 9-Micron 1-1/4" Abrasive Discs
- 94300 Dynaswivel®
- Wrenches for Accessory Changes
- Deluxe Storage/Carry Case



18058 Kit

Buffer

Model 18050

- 0 - 2,500 RPM free speed. Uses 5" to 8" diameter buffs.
- Insulated handle reduces cold air transmission to the operator.
- Common 5/8"-11 male spindle.
- Lightweight and compact in size.
- Rear exhaust, variable speed safety-lock lever throttle.
- Soft-grip handle can be positioned for right or left hand operation.
- Back-up pad (50853) and polishing bonnet (90082) not included.



Model 18050

Model Number	Motor hp	Motor RPM	Pad Size	Sound Level	Spindle Thread	Air Flow Rate CFM/SCFM	Air Inlet Thread	Hose Size	Air Pressure PSIG	Weight Pound	Length Inch	Height Inch
18050	.7	0-2,500	5" - 8"	87 dB(A)	5/8" - 11 male	3/27	1/4" NPT	3/8"	90	5.3	12	4
18055/18056	.4	2,400/3,200	3"	87 dB(A)	3/8" - 24 male	3/28	1/4" NPT	3/8"	90	2	10-3/8	2-1/2