


## DYNABRADE NITRO SERIES™ 3" EXTENDED BUFFER

Compact and lightweight the Dynabrade Nitro Series™ extended buffer is perfect for use in tight areas or contoured painted surfaces like side-view mirrors.

### FEATURES

- ▶ Tool includes 50126 Hook-Face Backup Pad
- ▶ Tactile, thermoplastic grip
- ▶ 3/8"-24 male spindle, rear exhaust
- ▶ Rotational rear exhaust directs cold air away from operator



### ROTARY MOTION

For Rotary  
Buffing



Model EB3

### DIAMETER

3" (76 mm)

### SPEED

2,700 RPM

### POWER

0.5 hp (373 W)

| Model Number | Sound Level | Spindle Thread | Maximum Air Flow SCFM (L/Min) | Hose I.D. Size Inch (mm) | Weight Pound (kg) | Height Inch (mm) | Length Inch (mm) |
|--------------|-------------|----------------|-------------------------------|--------------------------|-------------------|------------------|------------------|
| EB3          | 81 dB(A)    | 3/8" - 24 male | 26 (736)                      | 3/8 (10)                 | 1.6 (.72)         | 3 (76)           | 11.25 (286)      |

**Additional Specifications:** Air Inlet Thread 1/4" NPT • Air Pressure 90 PSIG (6.2 Bar)


**1 YEAR  
WARRANTY**

## DYNABRADE NITRO SERIES™ 5" - 8" BUFFER

Dynabrade Nitro Series™ buffers polish large areas like hoods and trunk lids quickly and with consistent results.

### FEATURES

- ▶ 2,800 RPM free speed. Accepts 5" to 8" diameter buffs
- ▶ Lightweight and compact in size
- ▶ Rear exhaust, variable speed safety-lock lever throttle
- ▶ Soft-grip handle can be positioned for right or left hand operation
- ▶ Insulated handle reduces cold air transmission to the operator
- \* Back-up pad (50853) and polishing bonnet (90082) not included



### ROTARY MOTION

For Rotary  
Buffing



Model RB1

### DIAMETER

5" - 8" (76 mm - 203 mm)

### SPEED

2,800 RPM

### POWER

1 hp (746 W)

| Model Number | Pad Size Inch (mm) | Sound Level | Spindle Thread | Maximum Air Flow SCFM (L/Min) | Hose I.D. Size Inch (mm) | Weight Pound (kg) | Height Inch (mm) | Length Inch (mm) |
|--------------|--------------------|-------------|----------------|-------------------------------|--------------------------|-------------------|------------------|------------------|
| RB1          | 8 (203)            | 89 dB(A)    | 5/8" - 11 Male | 48 (1359)                     | 3/8 (10)                 | 4.8 (122)         | 12.5 (318)       | 2.5 (64)         |
| RB2          | 8 (203)            | 89 dB(A)    | M14            | 48 (1359)                     | 3/8 (10)                 | 4.8 (122)         | 12.5 (318)       | 2.5 (64)         |

**Additional Specifications:** Air Inlet Thread 3/8" NPT • Hose I.D. Size 3/8" • Air Pressure 90 PSIG (6.2 Bar)