

Sabre Heavy-Duty

HIGHEST CCA capacity ranges (50-4000 CCA – 24V).

LARGE DISPLAY for less scrolling, more detailed instructions. It's also backlit for all light conditions.

INDUSTRY FIRST amp clamp connection ports for live amperage readings using optional external amp clamp.

15 FT. CABLE to perform tests from the cab of the vehicle.

FIELD UPDATEABLE to accommodate new battery types, system updates, feature additions.

Battery Testing

- Tests the following battery pack configurations:
 - One battery (6V or 12V)
 - Two batteries in series (24V); 2, 3, or 4 batteries in parallel (12V)
 - Two banks in parallel, each bank having 2 batteries in series (24V)
- Uses pack configuration in algorithm design.
- Step-by-step user instructions for easy test completion.
- Tester applied loads used on all pack combinations.

Electrical System Testing

- 12V and 24V charging system tests
- 12V and 24V starting system tests
- 12V and 24V diode tests
- Amp clamps available (not included) for starting/charging and current draw tests.

Features

Amp Clamp Connection – allows current drain tests and starting/charging analysis.

Tests Both FLA (flooded lead acid) and **AGM** (absorbed glass mat) battery types.

Scales – CCA, CA, AHR, MCA, JIS, DIN

User Definable – print header and footer.

Removable Test Cables – easily field replaceable.

PC Interface Port – allows for field updateable software.

IR Compatible – allows optional infrared wireless printer.

Readout Display – backlit for low light conditions, easy to view data in direct sunlight (4x20 character display).

Security Cable Connection – protects against stolen or dropped units.

Over-molded Surround with Soft-touch Keys – Ruggedly built, easy to use, even with gloves.

No. 3167-HD – Deluxe kit includes 24-Volt Heavy-Duty Battery Tester, 15 ft. test leads, instruction manual, molded plastic carrying case.

No. 3168-HD – Same as the 3167-HD above, but also includes an infrared wireless printer.

Accessories:

No. 3172-15 – 15 ft. Lead Set.

No. 3169 – Infrared Wireless Printer.

No. 3173 – Low Range Amp Probe (current drain tests).

No. 3174 – High Range Amp Probe (starting/charging test).

