

15-in-1 Multi-Bit Screwdriver/Nut Drivers

- Includes 14 different screwdriver tips plus a 1/4" (6.4 mm) nut driver
- Internal storage for screwdriver bits



INTERNAL STORAGE
in handle



32290



Cat. No.	Nut Driver Sizes	Phillips Bits	Slotted Bits	Square Bits	Hex Bits	Combo Bits	Torx® Bits	Other Bits	Shank Length	Overall Length
32290	1/4"	#0, #1, 2, #3	5/32" (4 mm), 1/4" (6.4 mm)	#1, #2	—	#1, #2	#10, #15, #20, #25	—	4" (101.6 mm)	8.5" (215.9 mm)
32291	1/4"	—	—	—	Pins: 1/8", 9/64", 5/32", 3/16"	—	Pins: #10, #15, #20, #25, #27, #30	Spanners: #6, #8, #10, #12	4" (101.6 mm)	8.5" (215.9 mm)
32292	1/4"	#0, #1, 2, #3	5/32" (4 mm), 1/4" (6.4 mm)	#1, #2	—	—	#10, #15, #20, #25	Schrader® Valve Insertion/Core Removal	4" (101.6 mm)	8.5" (215.9 mm)

Schrader® is a registered trademark of Schrader-Bridgeport International, Inc. TORX® is a registered trademark of Acument Intellectual Properties, LLC.

11-in-1 Multi-Bit Screwdriver/Nut Drivers

- Precision machined tip designed for combination head screws
- Cat. No. 32527 includes unique style bit for installation/removal of common TR-4 Schrader® valves and aggressive thread extractor tip for backing out broken cores which is great for HVAC and other industrial applications



32505



Cat. No.	Nut Driver Sizes	Phillips Bits	Slotted Bits	Square Bits	Combo Bits	TORX® Bits	Other Bits	Shank Length	Overall Length
32500	3/8", 5/16", 1/4"	#1, #2	1/4" (6.4 mm), 3/16" (4.8 mm)	#1, #2	—	T10, T15	—	3" (76.2 mm)	7.25" (184.2 mm)
32505	1/4", 5/16" 3/8"	#1, #2	1/4" (6.4 mm), 5/16" (7.9 mm)	#1, #2	#1, #2	—	—	4" (101.6 mm)	7.25" (184.2 mm)
32527	3/8", 5/16", 1/4"	#1, #2	1/4" (6.4 mm), 3/16" (4.8 mm)	#1, #2	—	—	Schrader® Valve Insertion/Core Removal	3" (76.2 mm)	7.75" (196.9 mm)

Schrader® is a registered trademark of Schrader International, Inc.

Multi-Bit Screwdriver/Nut Drivers

- Integrated screwdriver/nut driver shaft holds popular tips and converts nut driver sizes
- Cat. Nos. 32561 and 32562 compact design features standard 1-1/4" (32 mm) shaft allowing easy access to tight work spaces
- Cat No. 32577 has strong, heat-treated nut drivers for improved torque
- Cat. No. 32559 and 32560 have extended shafts and blades to provide 39% longer reach



32561

32557

32476

32559

Cat. No.	Description	Nut Driver Sizes	Phillips Bits	Slotted Bits	Square Bits	Hex Bits	TORX® Bits	Shank Length	Overall Length
32476	5-in-1	5/16"	#1, #2	1/4" (6.4 mm), 3/16" (4.8 mm)	—	—	—	4" (101.6 mm)	7.75" (196.9 mm)
32477	10-in-1	5/16", 1/4"	#1, #2	1/4" (6.4 mm), 3/16" (4.8 mm)	#1, #2	—	T10, T15	4" (101.6 mm)	7.75" (196.9 mm)
32557	6-in-1 Heavy-Duty	1/4", 5/16", 3/8"	#1, #2	1/4" (6.4 mm), 3/16" (4.8 mm)	#1, #2	3/8"	—	2.953" (75 mm)	7.891" (200.4 mm)
32559	6-in-1 Extended-Reach	1/4", 5/16"	#1, #2	1/4" (6.4 mm), 3/16" (4.8 mm)	—	—	—	4.109" (104.4 mm)	9.109" (231.4 mm)
32560	6-in-1 Extended-Reach	1/4", 5/16"	#2	1/4" (6.4 mm)	#1, #2	—	—	4.109" (104.4 mm)	9.109" (231.4 mm)
32561	6-in-1 Stubby	1/4", 5/16"	#1, #2	1/4" (6.4 mm), 3/16" (4.8 mm)	—	—	—	1.266" (32.2 mm)	3.406" (86.5 mm)
32562	6-in-1 Stubby	1/4", 5/16"	#2	3/16" (4.8 mm)	#1, #2	—	—	1.266" (32.2 mm)	3.406" (86.5 mm)

TORX® is a registered trademark of Acument Intellectual Properties, LLC



Additional bits and replacement bits can be found on page 77