

98061 **DIGITAL VACUUM GAUGE** in blow molded case
98061-C **DIGITAL VACUUM GAUGE** in a clamshell



SPECIFICATIONS:

- Response Time: 250 mSec.
- Sensor Cable: Spiral cable extended to 6.5 feet (2.6 meter)
- Sensor: Thermocouple sensor
- Connection Fitting: 1/4" flare female adapter
- Operating Temperature: 32 to 120°F (0 to 45°C)
- Power: 9V DC battery (AC/DC Adapter optional)
- Battery Life: 36 hours
- Low Battery Indicator: Special ICON on LCD
- Vacuum Units: Micron, Torr, mTorr, mmHg, mBar, Pa
- Range: 20,000 to 1 micron
- Accuracy Range*: ATM-1000 Microns: ±10% of reading
1000 - 100 Microns: ±7% of reading,
100 - 1 Micron: ±5% of reading

* Unit accuracy refers to sensor specifications and is based on optimal laboratory conditions. Field operations may greatly deviate from these levels.

Optional Accessories

98061-SENSOR	Replacement Sensor
99334-110	110 V AC/DC Adapter
99333	1/4 FL-M x 1/4 FL-M x 1/4 FL-F Tee

BLOWER FANS



- 120 Volts, 60 Hz
- Rated power: 2.0 Amp
- For indoor or outdoor use
- Variable speed switch controls motor speed: 950-1650 RPM
- Built-in overload protection
- (2 pcs) 11 amp built-in grounded receptacles
- Housing material: impact resistant ABS
- 8.5 ft cord length, SJTW 14 AWG
- 4-position adjustment feet

21200

1200 CFM BLOWER FAN

- Moves air up to: 1200 CFM
- Unit weight: 15.9 lbs

20300

300 CFM BLOWER FAN

- Moves air up to: 300 CFM
- Unit weight: 11.5 lbs

20300-HTR **HEATER ATTACHMENT FOR 300 CFM BLOWER FAN**



- 1320 Watts, 120 Volts
- 11 Amps, 5000 BTU
- Converts blower into a heater
- Clips securely onto the front of the blower and plugs into one of the outlets on the side of the blower
- 16 AWG SJT cord, grounded plug