



Mastercool®
"World Class Quality"

1 ASPEN DRIVE, RANDOLPH, NJ 07869
PHONE: 973-252-9119 / FAX: 973-252-2455
WEB: WWW.MASTERCOOL.COM

DIAGNOSTIC SMOKE MACHINES



43060-TB SPECIFICATIONS:

- Voltage: 12 VDC
- Input Pressure: Max 100 psi (7 bar)
- Output Pressure:
Internal Pump Max 22 psi (150 kPa)
External Pressure Source Max 28 psi (190 kPa)
- Safety Pressure Relief: 120 (±5) psi
- Oil Fill Line Indicator: 3.4 oz (100 ml (±10 ml))
- Flow Meter: 0 - 0.040 in. (0 - 1.0 mm)
- Dimensions: 11.8 x 8.1 x 11 in (300 x 205 x 280 mm)
- Weight: 11.5 lbs (5.2 Kg)
(Shipping Weight: 22 lbs (10 Kg))
- Power Consumption: Max 6.5 Amps
- Operating Temperature: 0 °F to 140°F (-17°C to 60°C)
- Operating Humidity: No Restrictions
- Operating Altitude: No Restrictions
- Vapor Output Hose: 10 feet
- Power Cable: 10 feet
- Pressure Supply: Air/Inert gas/Pump

43060-TB TURBO/INTAKE DIAGNOSTIC SMOKE MACHINE

For all turbo, intakes, exhaust, vacuum lines and vacuum components, manifolds, passenger compartment window and sunroof, headlight/tail-light fixtures and much more. Not for EVAP testing. This unit provides the option of compressed air, inert gases and a built-in internal compressor to inject the smoke into the system.

Accessories included: inflatable intake bladder, full set of block off caps, exhaust cone, high intensity battery powered smoke illuminating flashlight and 8 oz smoke producing fluid

FEATURES:

- Compact, heavy-duty design for years of reliable service
- Multiple options for smoke injection include built-in internal compressor, shop air and inert gases
- Quick smoke generation
- Built-in safety pressure relief valve
- Pressure can be regulated from 0 to 28 PSI
- Large easy to read pressure decay gauge 0 - 30 PSI
- Non-toxic and non-corrosive smoke
- 10' 12V power cables with durable clamps
- Heavy-duty 10' smoke injection hose
- Velcro strap for hose and power cable storage

AVAILABLE ACCESSORIES:

43060-DW-ST Diffuser Assembly - Short



43060-DW-ST