

COUPLERS  
PLUGS  
CAM/GROOVE

HOSE  
HOSE REELS  
HOSE FITTINGS

## PUSH-ON & LOCK ON AIR HOSE



Made of strong, flexible Nitrile with spiral synthetic yarn reinforcement. Resists oil, gasoline, abrasion and ozone. Highly resistant to petroleum based hydraulic oils. No clamps or ferrules needed, just cut hose to desired length and push on fitting. Ideal for automotive paint shop, construction, manufacturing and petrochemical industries. Use with compressed air, water and petroleum based solvents. Fittings are not included with bulk push and lock hose

- Maximum working pressure: 250 PSI
- Burst pressure: 1000 PSI
- Working temperature: -20°F to 210°F (-29°C to 100°C)
- Color: black

1627-100  
1627-250  
1627-500BK  
1629-100  
1629-250  
1629-500BK

Part No.	Hose ID	Hose OD	Length	Packaging
1627-100	1/4"	1/2"	100'	Dispensing Box
1627-250			250'	
1627-500BK			500'	Handy Reel
1629-100	3/8"	5/8"	100'	Dispensing Box
1629-250			250'	
1629-500BK			500'	Handy Reel

SEE PG. 27 FOR PUSH-ON & LOCK FITTINGS

## NYLON RE-KOIL AIR HOSE



Assembled with re-usable, full flow male NPT swivel fittings on both ends to avoid twisting and kinking. Individual display bag packaged. Resists abrasions

- Maximum working pressure: 200 PSI @ 70°F
- Working temperature: -40°F to 180°F (-40°C to 82°C)
- Material: nylon
- Color: yellow

1667  
1669  
1670  
1674  
1675  
1674-4  
1675-4

Part No.	Hose ID	Length	Swivel Male
1667	1/4"	12'	1/4"
1669		25'	
1669-100		100'	
1670	3/8"	50'	1/4"
1674		25'	3/8"
1674-4			1/4"
1675		50'	3/8"
1675-4			1/4"

Replacement fittings for nylon re-coil hose

Part No.	ID	NPT	Type
1669-1	1/4" Male	1/4"	Swivel Hose End
1675-1	3/8" Male	3/8"	
1675-5		1/4"	

## POLYURETHANE RE-KOIL AIR HOSE



Most flexible of all re-coil hoses has excellent shape retention. Resists abrasions, corrosive materials, oil & grease. Light & flexible completely assembled with 18" straight hose whip with swivel fittings on both ends. Individual display bag package

- Maximum working pressure: 125 PSI @ 70°F
- Working temperature: -50°F to 180°F (-46°C to 82°C)
- Material: polyurethane
- Color: yellow

1671-10  
1671-20  
1671-30  
1672-20  
1672-30  
1673-20

Part No.	Hose ID	Length	Swivel Male NPT
1671-10	1/4"	10'	1/4"
1671-20		20'	
1671-30		30'	
1672-20	3/8"	20'	3/8"
1672-30		30'	
1673-20		20'	

FRLs  
BLO-GUNS  
PUSH-TO-CONNECT

INFLATOR GAGES  
SERVICE GAGES

PRESSURE &  
SERVICE GAGES

GREASE GUNS

MERCHANDISERS