

400-6




400-6

SAFE-T-FLATE VALVE EXTENSION

- Inner dual wheel valve extension
- Fits all tube and tubeless valves in this section

Bulk Pkg Part No.	Retail Pkg Part No.	Per Card	Maximum Pressure	Effective Length (in)
400-6BK	s-400-6	2	150 PSI	8 1/4"

404 • 1455



404

1455

NICKEL PLATED VALVE CORES

Boxed Pkg Part No.	Bulk Part No.	Retail Pkg Part No.	Per Card	TR Number	Thread Size/Seal	Operating Temp	Pressure Range
404	404-100	s-404	5	TR-C1	• .2108-36 Thread • Red Teflon Seal	-40°F to 302°F	0-200 PSI
1455				TR-C2	• Large Bore • .302-32 Thread		

406



406

RIM HOLE REDUCER BUSHING

- For passenger cars, motorcycles, light trucks, and industrial vehicles

Boxed Pkg Part No.	Base Diameter	Sizes
406	2 1/4"	Reduces 5/8" to .453"

409



409

HI-PERFORMANCE TIRE VALVE

- Clamp-in type, brass chrome plated
- For use with mag, aluminum, exposed or reversed chrome wheels
- Sold complete with two grommets to fit .453 or .625 valve hole sizes

Boxed Pkg Part No.	Retail Pkg Part No.	Per Card	Max Pressure (cold inflation)	Rim Hole Diameter
409	s-409	1	80 PSI	.453" & .625"

413 • 414 • 415
418 • 423 • 425

413



414



415



418



423



425

SNAP-IN TUBELESS TIRE VALVES

- Cap thread size: .305-32
- Ozone resistant rubber
- Maximum cold inflation pressure may not exceed 60 PSI

Boxed Pkg Part No.	50-Pk Bulk Part No.	500-Pk Bulk Part No.	Retail Pkg Part No.	Per Card	TR Number	Rim Hole Diameter	Effective Length (in)
413-10	413-50	413-500	s-413	2	TR413	.453"	1 1/4"
414-10	414-50	414-500	s-414	2	TR414		1 1/2"
415-10	415-50	415-500	s-415	2	TR415	.625"	1 1/4"
418-10	418-50	418-500	s-418	2	TR418	.453"	2"
423-10	423-50	423-500	s-423	2	TR423		2 1/2"
425-10	425-50	425-500	s-425	2	TR425	.625"	2"