



Automotive Aftermarket Masking Solutions

IPG® and Norton are committed to a vision for the Automotive PBE Market to be recognized as a leader in performance masking, surface protection and complementary products – by upholding our customer commitment to deliver solutions that increase productivity, maintain product integrity, contain cost and promote environmental stewardship.



American® brand and Norton products have long been trusted by collision repair professionals for their unsurpassed quality and performance. But we do not rely only on our joint history or reputation. Our mission, as a team, is to build upon this proven performance and exceed the expectations of our customers in the automotive aftermarket.



SYNONYMOUS WITH OUTSTANDING MASKING PERFORMANCE!

American® brand Orange Mask® (OM) is a high performance masking tape developed to provide superior adhesion, UV resistance and high conformability. OM unwinds and applies smoothly and removes cleanly to deliver clean crisp paint lines. The superior solution for all automotive refinishers.

PERFORMANCE ADVANTAGES

- Sharp color separation on curves or straight lines
- Exceptional cornering
- Fine crepe paper backing ensures overall sharp paint lines
- Smooth to the touch – easy to work with
- High temperature resistance: 250°F (121°C) for 30 minutes
- 3 day UV resistance
- Excellent adhesion to backing when layered
- Smooth and controlled unwind
- Works with both solvent and waterborne paints
- Clean removal; stain resistant; resists bleed-through
- Superior for wet sanding applications
- Resists paint flaking



Part #	IPG Resource	Size	Case Qty
087143-00577	ORANGE MASK 12	12mm x 54.8m (0.47in x 60yd)	72 rolls
087143-00306	OM1855	18mm x 54.8m (0.70in x 60yd)	48 rolls
087143-00307	OM2455	24mm x 54.8m (0.94in x 60yd)	36 rolls
087143-00308	OM3655	36mm x 54.8m (1.41in x 60yd)	24 rolls
087143-00309	OM4855	48mm x 54.8m (1.88in x 60yd)	24 rolls
087143-00690	OM7655	76mm x 54.8m (2.99in x 60yd)	16 rolls



HAND MASK FILM

PREVENT OVERSPRAY WITH IPG's HAND MASK FILM!

IPG's Hand Mask is a pre-folded, high density polyethylene masking film designed for multiple transportation applications. The thick and durable 12 micron film is treated to resist overspray flaking during paint applications. This special film is designed with a reinforced top edge formulated to prevent the underlying film from sticking.

PERFORMANCE ADVANTAGES

- Corona-treated so paint won't flake off
- Durable film resists tearing; requires less tape
- Solvent resistant; no bleed-through
- Clings to surface, preventing overspray
- Designed to work with multiple hand dispensers
- 1" core fits most masking machines

in(mm) in the chart to the right indicates length of the material when unfolded.



Part #	IPG Resource	Size	Roll Height	Case Qty
087143-00214	HMF...24	24in x 180ft (609.6mm x 54.9m)	5.35in	12 rolls
087143-00215	HMF...36	36in x 90ft (914.4mm x 27.4m)	6.81in	12 rolls
087143-00216	HMF...48	48in x 180ft (1219.2mm x 54.9m)	8.78in	12 rolls
087143-00217	HMF...72	72in x 90ft (1828.8mm x 27.4m)	9.57in	12 rolls
087143-00218	HMF...99	99in x 90ft (2514.6mm x 27.4m)	13.0in	12 rolls

Product Physical Properties

Product	Backing	Adhesive	Total thickness (mils)	Tensile strength (lb/in of width)	Adhesion to steel (oz/in of width)	Elongation (% at break)	Temperature resistance	Color
OM	Fine crepe paper	Natural rubber/resin	7.1 (0.18mm)	23 (101 N/25mm)	27 (7.4 N/25mm)	12	250°F (121°C) 30 min	Orange
PG	Fine crepe paper	Natural rubber	7.3 (0.19mm)	26 (114 N/25mm)	28 (7.7 N/25mm)	10	250°F (121°C) 30 min	Beige
AM	Saturated crepe paper	Natural rubber/resin	6.6 (0.17mm)	20 (87.5 N/25mm)	28 (7.6 N/25mm)	12	225°F (107°C) 30 min	Aqua (blue-green)
MP	Crepe paper	Natural rubber	6.1 (0.155mm)	25 (109.5 N/25mm)	33 (9 N/25mm)	8	250°F (121°C) 1 hour	Beige
UG	Coarse crepe paper	Natural rubber	5.8 (0.15 mm)	23 (101 N/25mm)	34 (9.3 N/25mm)	14	175°F (80°C) 30 min	Beige
519	Crepe paper	Natural/synthetic rubber	6.0 (0.15mm)	23 (101 N/25mm)	36 (9.8 N/25mm)	7	180°F (82°C) 1 hour	Beige
TM27	Crepe paper/PET film	Rubber/resin	7.6 (0.19mm)	-	30 (8.2 N/25mm)	-	225°F (107°C) 1 hour	Natural



www.itape.com

American® brand is a registered trademark of Intertape Polymer Group® Inc. The Refinish Solutions Group logo is a pending trademark of Saint-Gobain Abrasives.

Distributed by:
Norton | Saint-Gobain
Automotive Aftermarket
www.nortonabrasives.com

Norton is a registered trademark of Saint-Gobain. The Refinish Solutions Group logo is a pending trademark of Saint-Gobain Abrasives.