

# THESE LIGHTS ARE ALWAYS READY FOR HAZARDOUS DUTY.

## 3N PROPOLYMER® LED

Lightweight, alkaline battery-powered personal light with 3 ultra-bright LEDs. Long run time. Impact-resistant body and face cap. Unbreakable, polycarbonate scratch-resistant lens. Push-button tail switch for momentary and on-off operation.

### 3N PROPOLYMER LED

**BATTERY:** 3 "N" size alkaline

**SIZE:** 5.25" x .96" x .69"  
(13.33 x 2.44 x 1.75 cm)

**WEIGHT:** 2.1 OZ (59.54 g)

**COLOR:** Yellow or Black

62202 White LEDs and alkaline batteries — Yellow

62302 White LEDs and alkaline batteries — Black

|                  |     |
|------------------|-----|
| <b>LUMENS:</b>   | 30  |
| <b>CANDELA:</b>  | 300 |
| <b>DISTANCE:</b> | 35m |
| <b>RUN TIME:</b> | 10h |



Class I, II, Div. 1, Groups A,B,C,D,E,F,G;  
Class III, Exia, T4A Classified



## POLYSTINGER® LED HAZ-LO®

If you need a Class 1, Div. 1 rated light with the cost savings of a rechargeable, the PolyStinger LED HAZ-LO is the light you need. Not only does it provide a bright-white light, it is also intrinsically safe and has an unbreakable, scratch resistant lens. It's O-ring sealed and is IPX4 rated for water resistance and is 3 meter impact resistance tested.

### POLYSTINGER LED HAZ-LO

**BATTERY:** NiCd

**SIZE:** 10.2" x 1.76" x 1.34"  
(25.9 x 4.47 x 3.4 cm)

**WEIGHT:** 13.5 OZ (382 g)

**COLOR:** Black or Yellow

### YELLOW BLACK

76412 76442 120V AC/12V DC

76411 76441 12V DC

76410 76440 Without Charger

### ACCESSORIES

76409 Lanyard

75928 Loop Holster

75906 Ring Holder

76375 NiCd Battery Stick

75400 5 Unit Bank Smart Charger 120V

75103 Charger Holder Fast Charge (2.5 hr)

75105 Charger Holder Stinger (10 hr)

22060 120V AC Charge Cord

22051 DC1 Charge Cord

22050 DC2 Direct Wire Charge Cord

### TRADITION SERIES

|                  | HIGH   | LOW   |
|------------------|--------|-------|
| <b>LUMENS:</b>   | 130    | 50    |
| <b>CANDELA:</b>  | 15,000 | 5,700 |
| <b>DISTANCE:</b> | 245m   | 151m  |
| <b>RUN TIME:</b> | 4h     | 12h   |

Moonlight mode: 20 days of continuous run time



Lanyard Ring  
with lanyard for tail cap.



Class I & II, Division 1, Groups C,D,F,G;  
Class I, Division 2, Groups A,B,C,D.;  
Class III; 138 C, T-Code: T3C

### Special Features:

- Non-conductive, corrosion-resistant body.
- IPX4-rated for water-resistance.
- 3 meter impact-resistance tested.