

BUILT FOR DURABILITY AND PERFORMANCE.

POLYSTINGER® LED HAZ-LO®

If you're working in a potentially hazardous location, this is the light you need. It provides lots of bright, white light, yet it's intrinsically safe, with a Class I, Div. 1. rating. It has an O-ring sealed, unbreakable, scratch-resistant lens. It's IPX4 rated for water-resistance, and 3 meter impact-resistance tested.

	HIGH	LOW
LUMENS:	130	50
CANDELA:	15,000	5,700
DISTANCE:	245m	151m
RUN TIME:	4h	12h

Moonlight mode: 20 days of continuous run time

TRADITION SERIES



Lanyard Ring
with lanyard for tail cap.

TRADITION SERIES

POLYSTINGER LED HAZ-LO

BATTERY: NiCd Rechargeable

SIZE: 10.2" x 1.76" x 1.34"
(25.9 x 4.47 x 3.4 cm)

WEIGHT: 13.5 oz (382 g)

COLOR: Black or Yellow



SGS
Class I & II, Division 1, Groups C,D,F,G;
Class I, Division 2, Groups A,B,C,D;
Class III; 138 C, T-Code: T3C

YELLOW BLACK

76412	76442	120V AC/12V DC Smart Charger
76411	76441	12V DC Smart Charger
76410	76440	Without Charger

ACCESSORIES

76409	Lanyard
75928	Loop Holster
75906	Ring Holder
76375	NiCd Battery Stick
75400	5 Unit Bank Smart Charger 120V
22060	120V AC Charge Cord
22051	DC1 Charge Cord
22050	DC2 Direct Wire Charge Cord

POLYSTINGER DS® LED POLYSTINGER® LED

Intense brightness, long-range and long run time in a durable nylon polymer housing. It's the ideal combination of power, performance and durability. The DS model has the convenience of two full-function, independent switches: one on the head and a tail switch.

	HIGH	MEDIUM	LOW
LUMENS:	485	240	120
CANDELA:	28,000	14,000	7,000
DISTANCE:	335m	237m	167m
RUN TIME:	3h	5h 30m	10h

Strobe mode: 7.5 hours of continuous run time

TRADITION SERIES



TRADITION SERIES



With [(STROBE)]
Double tap switch to activate.

AVAILABLE IN BOTH DUAL SWITCH AND STANDARD STYLES

POLYSTINGER DS LED

BATTERY: NiMH Rechargeable

DS SIZE: 8.64" x 1.76" x 1.21"
(21.95 x 4.47 x 3.07 cm)

DS WEIGHT: 11.9 oz (338 g)

DS COLOR: Black

POLYSTINGER LED

BATTERY: NiMH Rechargeable

SIZE: 8.07" x 1.76" x 1.21"
(20.50 x 4.47 x 3.07 cm)

WEIGHT: 11.5 oz (326 g)

COLOR: Black or Yellow

DS LED	LED	
—	76163	120V AC/DC 2 Holders—Yellow
76813	76113	120V AC/DC 2 Holders—Black
—	76161	120V AC—Yellow
76811	76111	120V AC—Black
—	76199	12V DC—Yellow
76849	76149	12V DC—Black
—	76182	120V AC/DC 1 PiggyBack Holder—Yellow
76832	76132	120V AC/DC 1 PiggyBack Holder—Black
—	76203	Without Charger—Yellow
76850	76150	Without Charger—Black

STINGER ACCESSORIES

At Streamlight, we engineer the highest performing, most rugged, durable and innovative lights on the market. In addition, we support them with the accessories you can depend on and the options and configurations that you need to accommodate all your portable lighting needs.

Stinger Accessories	DS LED HL LED HL	DS HPL HPL	DS LED LED	UltraStinger LED	Stinger Switchblade	PolyStinger LED HAZ-LO	PolyStinger LED / DS LED
5 Unit Bank Charger 	75400	75400	75400	75400	75400	75400	75400
Smart Charger 	75105	75105	75105	75105	75105	75105	75105
Steady Piggyback® 	75277	75277	75277	—	—	75277	75277
NiCd Battery Stick 	—	—	—	—	—	76375	—
NiMH Battery Stick 	75375	75375	75375	77375	—	—	75375
Li-Ion Battery Stick 	75176	75176	75176	75176	76805	—	75176
12V Cig Charge Cord 	22051	22051	22051	22051	22051	22051	22051
12V DC Charge Cord 	22050	22050	22050	22050	22050	22050	22050
120V AC Charge Cord 	22071	22071	22071	22071	22071	22071	22071
Leather Plain Holster 	75133	—	75133	—	—	—	75133
Leather Weave Holster 	75134	—	75134	—	—	—	75134
Std. Nylon Holster 	75927	75927	75927	—	—	—	75910
Loop Nylon Holster 	75928	75928	75928	75928	—	75928	75928
Duty Holster 	88053	88053	88053	88053	—	—	—
Ring Holder 	75906	75906	75906	75906	—	75906	75906
Red Flip Lens 	75115	—	75115	—	—	—	—
Green Flip Lens 	75117	—	75117	—	—	—	—
Blue Flip Lens 	75116	—	75116	—	—	—	—
Red Wand 	75903	75946	75903	78903	—	—	75933
White Wand 	75908	75949	75908	78908	—	—	75938
Blue Wand 	75902	75947	75902	—	—	—	75932
Yellow Wand 	75904	75948	75904	78904	—	—	75934
Glow Wand 	75913	75950	75913	78913	—	—	75943
USB Cord - 5" 	22079	22079	22079	—	22079	—	—
USB Cord - 22" 	22070	22070	22070	—	22070	—	—
USB Cord - 40" 	22081	22081	22081	—	22081	—	—
12V DC USB Adapter 	22069	22069	22069	—	22069	—	—
100V/120V AC USB Adapter 	22058	22058	22058	—	22058	—	—

THESE LIGHTS ARE ALWAYS READY FOR HAZARDOUS DUTY.

3N PROPOLYMER® LED

Lightweight, alkaline battery-powered personal light with 3 ultra-bright LEDs. Long run time. Impact-resistant body and face cap. Unbreakable, polycarbonate scratch-resistant lens. Push-button tail switch for momentary and on-off operation.

3N PROPOLYMER LED

BATTERY: 3 "N" size alkaline

SIZE: 5.25" x .96" x .69"
(13.33 x 2.44 x 1.75 cm)

WEIGHT: 2.1 OZ (59.54 g)

COLOR: Yellow or Black

62202 White LEDs and alkaline batteries — Yellow

62302 White LEDs and alkaline batteries — Black

LUMENS:	30
CANDELA:	300
DISTANCE:	35m
RUN TIME:	10h



Class I, II, Div. 1, Groups A,B,C,D,E,F,G;
Class III, Exia, T4A Classified



POLYSTINGER® LED HAZ-LO®

If you need a Class 1, Div. 1 rated light with the cost savings of a rechargeable, the PolyStinger LED HAZ-LO is the light you need. Not only does it provide a bright-white light, it is also intrinsically safe and has an unbreakable, scratch resistant lens. It's O-ring sealed and is IPX4 rated for water resistance and is 3 meter impact resistance tested.

POLYSTINGER LED HAZ-LO

BATTERY: NiCd

SIZE: 10.2" x 1.76" x 1.34"
(25.9 x 4.47 x 3.4 cm)

WEIGHT: 13.5 OZ (382 g)

COLOR: Black or Yellow

YELLOW BLACK

76412 76442 120V AC/12V DC

76411 76441 12V DC

76410 76440 Without Charger

ACCESSORIES

76409 Lanyard

75928 Loop Holster

75906 Ring Holder

76375 NiCd Battery Stick

75400 5 Unit Bank Smart Charger 120V

75103 Charger Holder Fast Charge (2.5 hr)

75105 Charger Holder Stinger (10 hr)

22060 120V AC Charge Cord

22051 DC1 Charge Cord

22050 DC2 Direct Wire Charge Cord

TRADITION SERIES

	HIGH	LOW
LUMENS:	130	50
CANDELA:	15,000	5,700
DISTANCE:	245m	151m
RUN TIME:	4h	12h

Moonlight mode: 20 days of continuous run time



Lanyard Ring
with lanyard for tail cap.



Class I & II, Division 1, Groups C,D,F,G;
Class I, Division 2, Groups A,B,C,D.;
Class III; 138 C, T-Code: T3C

Special Features:

- Non-conductive, corrosion-resistant body.
- IPX4-rated for water-resistance.
- 3 meter impact-resistance tested.