

BUILT FOR DURABILITY AND PERFORMANCE.

POLYSTINGER® LED HAZ-LO®

If you're working in a potentially hazardous location, this is the light you need. It provides lots of bright, white light, yet it's intrinsically safe, with a Class I, Div. 1. rating. It has an O-ring sealed, unbreakable, scratch-resistant lens. It's IPX4 rated for water-resistance, and 3 meter impact-resistance tested.

	HIGH	LOW
LUMENS:	130	50
CANDELA:	15,000	5,700
DISTANCE:	245m	151m
RUN TIME:	4h	12h

Moonlight mode: 20 days of continuous run time

TRADITION SERIES



Lanyard Ring
with lanyard for tail cap.

TRADITION SERIES

POLYSTINGER LED HAZ-LO

BATTERY: NiCd Rechargeable

SIZE: 10.2" x 1.76" x 1.34"
(25.9 x 4.47 x 3.4 cm)

WEIGHT: 13.5 oz (382 g)

COLOR: Black or Yellow



SGS
Class I & II, Division 1, Groups C,D,F,G;
Class I, Division 2, Groups A,B,C,D;
Class III; 138 C, T-Code: T3C

YELLOW BLACK

76412	76442	120V AC/12V DC Smart Charger
76411	76441	12V DC Smart Charger
76410	76440	Without Charger

ACCESSORIES

76409	Lanyard
75928	Loop Holster
75906	Ring Holder
76375	NiCd Battery Stick
75400	5 Unit Bank Smart Charger 120V
22060	120V AC Charge Cord
22051	DC1 Charge Cord
22050	DC2 Direct Wire Charge Cord

POLYSTINGER DS® LED POLYSTINGER® LED

Intense brightness, long-range and long run time in a durable nylon polymer housing. It's the ideal combination of power, performance and durability. The DS model has the convenience of two full-function, independent switches: one on the head and a tail switch.

	HIGH	MEDIUM	LOW
LUMENS:	485	240	120
CANDELA:	28,000	14,000	7,000
DISTANCE:	335m	237m	167m
RUN TIME:	3h	5h 30m	10h

Strobe mode: 7.5 hours of continuous run time

TRADITION SERIES



TRADITION SERIES



With [(STROBE)]
Double tap switch to activate.

AVAILABLE IN BOTH DUAL SWITCH AND STANDARD STYLES

POLYSTINGER DS LED

BATTERY: NiMH Rechargeable

DS SIZE: 8.64" x 1.76" x 1.21"
(21.95 x 4.47 x 3.07 cm)

DS WEIGHT: 11.9 oz (338 g)

DS COLOR: Black

POLYSTINGER LED

BATTERY: NiMH Rechargeable

SIZE: 8.07" x 1.76" x 1.21"
(20.50 x 4.47 x 3.07 cm)

WEIGHT: 11.5 oz (326 g)

COLOR: Black or Yellow

DS LED	LED	
—	76163	120V AC/DC 2 Holders—Yellow
76813	76113	120V AC/DC 2 Holders—Black
—	76161	120V AC—Yellow
76811	76111	120V AC—Black
—	76199	12V DC—Yellow
76849	76149	12V DC—Black
—	76182	120V AC/DC 1 PiggyBack Holder—Yellow
76832	76132	120V AC/DC 1 PiggyBack Holder—Black
—	76203	Without Charger—Yellow
76850	76150	Without Charger—Black

THESE LIGHTS ARE ALWAYS READY FOR HAZARDOUS DUTY.

3N PROPOLYMER® LED

Lightweight, alkaline battery-powered personal light with 3 ultra-bright LEDs. Long run time. Impact-resistant body and face cap. Unbreakable, polycarbonate scratch-resistant lens. Push-button tail switch for momentary and on-off operation.

3N PROPOLYMER LED

BATTERY: 3 "N" size alkaline

SIZE: 5.25" x .96" x .69"
(13.33 x 2.44 x 1.75 cm)

WEIGHT: 2.1 OZ (59.54 g)

COLOR: Yellow or Black

62202 White LEDs and alkaline batteries — Yellow

62302 White LEDs and alkaline batteries — Black

LUMENS:	30
CANDELA:	300
DISTANCE:	35m
RUN TIME:	10h



Class I, II, Div. 1, Groups A,B,C,D,E,F,G;
Class III, Exia, T4A Classified



POLYSTINGER® LED HAZ-LO®

If you need a Class 1, Div. 1 rated light with the cost savings of a rechargeable, the PolyStinger LED HAZ-LO is the light you need. Not only does it provide a bright-white light, it is also intrinsically safe and has an unbreakable, scratch resistant lens. It's O-ring sealed and is IPX4 rated for water resistance and is 3 meter impact resistance tested.

POLYSTINGER LED HAZ-LO

BATTERY: NiCd

SIZE: 10.2" x 1.76" x 1.34"
(25.9 x 4.47 x 3.4 cm)

WEIGHT: 13.5 OZ (382 g)

COLOR: Black or Yellow

YELLOW BLACK

76412 76442 120V AC/12V DC

76411 76441 12V DC

76410 76440 Without Charger

ACCESSORIES

76409 Lanyard

75928 Loop Holster

75906 Ring Holder

76375 NiCd Battery Stick

75400 5 Unit Bank Smart Charger 120V

75103 Charger Holder Fast Charge (2.5 hr)

75105 Charger Holder Stinger (10 hr)

22060 120V AC Charge Cord

22051 DC1 Charge Cord

22050 DC2 Direct Wire Charge Cord

TRADITION SERIES

	HIGH	LOW
LUMENS:	130	50
CANDELA:	15,000	5,700
DISTANCE:	245m	151m
RUN TIME:	4h	12h

Moonlight mode: 20 days of continuous run time



Lanyard Ring
with lanyard for tail cap.



Class I & II, Division 1, Groups C,D,F,G;
Class I, Division 2, Groups A,B,C,D.;
Class III; 138 C, T-Code: T3C

Special Features:

- Non-conductive, corrosion-resistant body.
- IPX4-rated for water-resistance.
- 3 meter impact-resistance tested.