



4420AH

### FULLY WELDED BOTTLE JACKS

- Fully welded base and top prevents oil leakage over time and improves durability
- Built-in safety valve protects against dangerous ram overextension
- Extension screw adjusts to desired work height for added reach

4402 - 2 TON

4404 - 4 TON

4406 - 6 TON

4408 - 8 TON

4412 - 12 TON

4412S - 12 TON SHORT

4412AH - 12 TON AIR/HYDRAULIC

4420 - 20 TON

4420S - 20 TON SHORT

4420AH - 20 TON AIR/HYDRAULIC

4430 - 30 TON

4450 - 50 TON



MODEL #	CAPACITY (TONS)	LOW HEIGHT (IN.)	HIGH HEIGHT (IN.)	BASE WIDTH (IN.)	BASE LENGTH (IN.)	OVERALL HEIGHT (IN.)	HANDLE LENGTH (IN.)	SHIPPING WEIGHT (LBS.)
4402	2	7.1	13.6	3.9	3.66	7.1	11	5.5
4404	4	7.6	14.7	4.33	4.06	7.6	11	7.3
4406	6	8.3	16.3	4.8	4.53	8.3	11	9.9
4408	8	9.1	18.1	5.2	4.72	9.1	13.5	11.5
4412	12	9.1	17.3	5.71	4.96	9.1	16.5	14.3
4412S	12 - Short	7.5	14.4	5.71	4.96	7.5	16.54	12.8
4412AH	12	9.6	18.7	8.07	5.91	9.1	25.5	29.8
4420	20	9.5	17.8	6.42	5.63	9.5	16.5	20.5
4420S	20 - Short	7.5	13.8	6.42	5.63	7.5	16.5	17.9
4420AH	20	9.6	18.7	8.66	6.89	9.5	25.5	38.3
4430	30	11	17.5	6.81	6.02	10.8	16.5	26.9
4450	50	11.8	18.8	8.27	6.93	10.4	16.5	56.5