



5002A

5001A

BENCH GRINDERS WITH LIGHT

- Bright, flexible work light
- Has two grit wheels: coarse 36 and medium 60
- Each wheel has protective spark guard and adjustable eye shield
- Mounting holes and rubber feet make grinder easy to mount on a stand (optional - part #5003 or 5005A) or use on an approved work table or workbench
- Cast iron base for durability
- Ball bearing construction for smooth operation
- 1/2" Arbor accepts standard 6" wheel
- UL & CSA Listed and meets OSHA requirements

5001A

5002A

MODEL	POWER	NO LOAD SPEED	MOTOR	VOLTAGE
5001A	1/2 HP Motor	3450 RPM	3.5 Amp	115V/60Hz
5002A	3/4 HP Motor	3450 RPM	5 Amp	115V/60Hz

Replacement eye shields - RS500119B (5001A), RS500219B (5002A)

Replacement tool rests - RS500135B



BENCH GRINDER STAND

- Sturdy base with pre-drilled holes for mounting on floors
- Use with 5001A & 5002A and other 6" or 8" bench grinders

5003

SPECS	SIZE
Base Mounting Area (in.)	10.5 x 7.5
Height (in.)	36
PIPE SHAFT DIMENSIONS	SIZE
Diameter (in.)	3
Height (in.)	26.63



16 SPEED FLOOR UL/CSA DRILL PRESS

- Heavy duty 3/4 HP motor with 5/8" drill capacity
- Convenient belt tension lever for quick speed transition
- Table rotates 360° and pivots from 0° to 45° on each side with indicator to facilitate settings
- UL & CSA Listed

5000A

SPECS	SIZE
Power	3/4 HP
Power Source	115V/60Hz
Speeds Range	200 - 3850 RPM
Max Spindle Stroke (in.)	3.13
Spindle Nose	#2
Diameter of Column (in.)	2.75
Table Diameter (in.)	11.5
Height (in.)	61.8

Replacement 5/8" chuck & key - RS5000A87 (Fits standard MT2 Arbor)