

JBC SERIES HEAVY-DUTY BEAM CLAMPS

FEATURES

- Welded, fully enclosed pockets provide greater stability and durability where the beam clamp attaches to the beam/structure
- Larger, thicker diameter pins for increased durability and life

DURABILITY

- Welded all-steel frame and powder coat finish provide maximum durability and protection
- Clamp jaw is designed to distribute the load away from the beam flange edge increasing safety
- Used for quick mounting of a hoist to a broad range of beams

STANDARDS

- This product complies with ANSI / ASME B30.11 and B30.17 Standards
- Load tested to 125% of capacity with certificate

STOCK NUMBER	252710	252720	252730	252750
Model Number	JBC-1	JBC-2	JBC-3	JBC-5
Capacity (T)	1	2	3	5
Capacity (lbs.)	2200	4400	6600	11000
Beam Flange Capacity (min. / max / in.)	2-31/32 - 8-5/8	2-31/32 - 8-5/8	3-15/16 - 9-5/8	4-15/16 - 10-5/8
Weight (lbs.)	12	14	27	34



HD SERIES LARGE CAPACITY BEAM CLAMPS

FEATURES

- Welded, enclosed pockets provide greater stability and durability where the beam clamp attaches to the beam/structure
- Twin reinforcing clamp jaw pins for increased clamping stability and durability

DURABILITY

- Welded all-steel frame and powder coat finish provide maximum durability and protection
- Clamp jaw is designed to distribute the load away from the beam flange edge increasing safety
- Used for quick mounting of a hoist to a broad range of beams

STANDARDS

- This product complies with ANSI / ASME B30.11 and B30.17 Standards
- Load tested to 125% of capacity with certificate

STOCK NUMBER	202710	202720	202730	202750
Model Number	HD-1T	HD-2T	HD-3T	HD-5T
Capacity (T)	1	2	3	5
Capacity (lbs.)	2200	4400	6600	11000
Beam Flange Capacity (min. / max / in.)	2-15/16 - 8-11/16	2-15/16 - 8-11/16	3-1/8 - 12-5/8	3-9/16 - 12-5/8
Weight (lbs.)	10	11	21	24

