

JLH SERIES COMPACT LEVER HOISTS

SAFETY

- Weston® brake design with opposing double pawls, splits the load to opposite sides of the ratchet gear for greater load security
- Industrial rated alloy steel hooks rotate 360° for easy rigging and slowly stretch to indicate an overload situation

DURABILITY

- Grade 100 load chain is a smaller, more compact link with a greater working load limit and is Zinc plated for maximum corrosion protection
- The 4 pocket chain sprocket provides enhanced chain and lift wheel engagement for reduced vibration and smooth lifting
- Secured with Allen screws and lock nuts, the cast-steel safety latches are more durable than stamped steel latches and will not bend out of compliance with lifting regulations
- Durable, impact resistant, aluminum alloy housings makes the JLH Compact lever hoist one of the lightest hoists on the market
- Intended for the harshest environments, the heat-treated load plates and case hardened corrosive resistant internal parts extend the life of the hoist
- Every JLH Compact Lever Hoist includes as standard equipment a rugged vinyl pouch with belt loops and carrying strap

STANDARDS

- This product complies with ANSI / ASME B30.21 and HST-3 Standards
- Load tested to 125% of capacity with certificate

STOCK NUMBER	MODEL NUMBER	CAPACITY (T)	CAPACITY (lbs.)	STANDARD LIFT (ft.)	HEADROOM (in.)	LOAD CHAIN (dia/mm) X NO. OF FALLS	LEVER LENGTH (in.)	LBS. OF PULL TO LIFT CAPACITY	WEIGHT (lbs.)	REPLACEMENT PARTS	REPLACEMENT PART STOCK NO.
JLH SERIES LEVER HOISTS - 1/4 TON											
181205	JLH-25-5	1/4	500	5	7-9/10	3.2 x 1	5-3/4	45	3-1/2	Top Hook	JLH25-1G
181210	JLH-25-10	1/4	500	10	7-9/10	3.2 x 1	5-3/4	45	4-2/5	Bottom Hook	JLH25-4G
181215	JLH-25-15	1/4	500	15	7-9/10	3.2 x 1	5-3/4	45	5-2/7	Safety Latch Kit	JLH25-2
JLH SERIES LEVER HOISTS - 1/2 TON											
181505	JLH-50-5	1/2	1000	5	9-7/10	4.3 x 1	6-3/10	54	5-1/2	Top Hook	JLH50-1G
181510	JLH-50-10	1/2	1000	10	9-7/10	4.3 x 1	6-3/10	54	7	Bottom Hook	JLH50-4G
181515	JLH-50-15	1/2	1000	15	9-7/10	4.3 x 1	6-3/10	54	8-3/5	Safety Latch Kit	JLH50-2

*CUSTOM LIFTS AVAILABLE IN ALL CAPACITIES IN 10 FT INCREMENTS



JLP-A SERIES MINI-PULLERS

SAFETY

- Weston® brake design with opposing double pawls, splits the load to opposite sides of the ratchet gear for greater load security
- Industrial rated alloy steel hooks rotate 360° for easy rigging and slowly stretch to indicate an overload situation

DURABILITY

- Intended for the harshest environments, the heat-treated load plates and case hardened corrosive resistant internal parts extend the life of the hoist
- The lightweight design with shorter handle and smaller body are ideal for confined areas and low headroom applications
- Grade 80 load chain is black oxide coated for standard corrosion resistance
- Impact resistant all steel construction for added durability and protection

STANDARDS

- This product complies with ANSI / ASME B30.21 and HST-3 Standards
- Load tested to 125% of capacity with certificate

STOCK NUMBER	MODEL NUMBER	CAPACITY (T)	CAPACITY (lbs.)	STANDARD LIFT (ft.)	HEADROOM (in.)	LOAD CHAIN (dia/mm) X NO. OF FALLS	LEVER LENGTH (in.)	LBS. OF PULL TO LIFT CAPACITY	WEIGHT (lbs.)	REPLACEMENT PARTS	REPLACEMENT PART STOCK NO.
JLP-A SERIES LEVER HOISTS - 1/4 TON											
287100	JLP-025A-5	1/4	500	5	8-1/4	4 x 1	6	60	4-5/9	Top Hook	JLP25A-26G
287101	JLP-025A-10	1/4	500	10	8-1/4	4 x 1	6	60	5-5/6	Bottom Hook	JLP25A-38G
287102	JLP-025A-15	1/4	500	15	8-1/4	4 x 1	6	60	7	Safety Latch Kit	JLP25A-27-1
JLP-A SERIES LEVER HOISTS - 1/2 TON											
287200	JLP-050A-5	1/2	1000	5	10	4.3 x 1	8-1/2	86	5-1/6	Top Hook	JLP50A-26G
287201	JLP-050A-10	1/2	1000	10	10	4.3 x 1	8-1/2	86	6-5/6	Bottom Hook	JLP50A-38G
287202	JLP-050A-15	1/2	1000	15	10	4.3 x 1	8-1/2	86	8-1/3	Safety Latch Kit	JLP50A-27-1

*CUSTOM LIFTS AVAILABLE IN ALL CAPACITIES IN 10 FT INCREMENTS

