

10" x 16" HORIZONTAL BANDSAW



DURABILITY

- Heavy-duty rugged transmission utilizes hardened and ground gears operating in an oil bath
- One piece wheel cover
- Cast iron blade wheels
- Bi-Metal Blade

SAFETY

- Exclusive adjustable blade guide with six contact point system that utilizes cam follower bearings mounted on eccentric shafts on both sides of the blades

EASE OF USE

- Swivel control panel puts sawing functions at operator's fingertips
- Variable speed drive system allows the operator to fine tune the blade speed fast and easily
- Patented 3-Jaw vise with rapid action moveable jaw for faster set up
- Adjustable material stop
- Large one piece wheel cover
- Coolant system

STOCK NUMBER	414472	414478	414499
Model Number	J-7020	J-7040	J-7040-4
CUTTING CAPACITIES			
Round Capacity at 90° (in.)	10	10	10
Round Capacity at 45° (in.)	10	10	10
Rectangle Capacity at 90° (in.)	7 x 16 / 10 x 10	7 x 16 / 10 x 10	7 x 16 / 10 x 10
Rectangle Capacity at 45° (in.)	6-1/2 x 11	6-1/2 x 11	6-1/2 x 11
Blade Size (in.)	1 x .035 x 130	1 x .035 x 130	1 x .035 x 130
Blade Wheel Diameter (in.)	14	14	14
Blade Speed (sfpm)	100 - 350	100 - 350	100 - 350
Bed Height (in.)	23-1/2	23-1/2	23-1/2
Motor (HP)	1-1/2HP, 115/230V, 1Ph, Prewired 230V	2HP, 230V, 3Ph	2HP, 460V, 3Ph, Prewired 460V
Floor Space Required (L x W x H / in.)	75-1/2 x 33 x 41	75-1/2 x 33 x 41	75-1/2 x 33 x 41
Net Weight (lbs.)	927	927	927

OPTIONAL EQUIPMENT	STOCK NUMBER
Replacement Blade - 1" x .035" x 135" x 4/6VT	5674011
Replacement Blade - 1" x .035" x 135" x 5/8VT	5674022
Replacement Blade - 1" x .035" x 135" x 6/10VT	5674021

