

22-44 PRO DRUM SANDER



FEATURES

- Exclusive SandSmart™ infinitely variable-feed control produces the ultimate finish at a rate of up to 10 feet per minute and prevents machine overload
- Digital read-out for more accurate sanding
- Patented conveyor belt TRACKERS™ dramatically reduce the need for manual belt adjustments
- 22" wide suspended drum is supported on both ends with a truss-like carriage arm for greater strength and easy alignment to the table surface for consistent performance
- Sealed and permanently lubricated drum ball bearings for longer life
- Precision-flattened reinforced steel conveyor bed and no-give power feed belt provide a constant smooth sanding action for better results
- Adjustable drum height and downward pressure feature virtually eliminates snipe
- Large cast-iron handwheel adjusts height at 3/32" per turn for precise sanding thickness control
- Patented abrasive take-up fasteners make changing abrasives quick and easy
- Depth gauge has locking stop to ensure accuracy

OPTIONAL ACCESSORIES

Tuf Tool	98-0060
Powerfeed Belt 22"- 120G	60-0321-P



STOCK NUMBER		649600
Model Number	22-44 PRO	
Conveyor Motor	43 in.-lbs. torque, direct drive, dc	
Conveyor Speed (FPM)	0 - 10	
Drum Diameter (In.)	5	
Drum Length (In.)	22	
Drum Speed (RPM)	1600	
Dust Port Outside Diameter (In.)	4	
Maximum Board Thickness (In.)	4	
Maximum Board Width (In.)	44	
Minimum Board Length (In.)	2-1/4	
Minimum Board Thickness (In.)	1/32	
Motor Amps	8	
Motor Phase (PH)	1	
Motor Power (HP)	3	
Motor Voltage (V)	230	
Prewired Voltage (V)	230	
Net Weight (lbs.)	394	